




FRP Pultrusion Machine



Model	1 by 1	1 by 2	1 by 4
Number of Winding Head	1	2	4
Product Diameter Range	D4mm-40mm	D4mm-22mm	D4mm-16mm
Daily Capacity(D8mm)	3600m	7200m	14400m
Winding Rotation Rate	0-200rpm	0-200rpm	0-200rpm
Winding Power	1.1kw	2.2kw	2.2kw
Oven Power	6kw	12kw	24kw

Equipment Component

The machine set is mainly composed of yarn guide board, resin bath with shelf (including pre-forming device), winding part, heating temperature control part, traction part, length measuring device, electric control system and so on.



Resin Bath with Shelf



Control Panel



Heating Temperature Control Part



Traction Part

THE SPECIFICATIONS

- ◆ All the electrical parts, motor, reducer and transmission parts adopt the famous brand.
- ◆ High accuracy instruments are used to monitor and control the complete line, the important datas can be shown directly on the control panel.
- ◆ Each heating and curing area is controlled by a separate temperature control instrument with accuracy of 1 °C.
- ◆ The dragger feet are made of high quality PU block, which is durable and long service life.
- ◆ The resin bath system material is stainless steel, it have a water bath heating and temperature control system to ensure that the resin is always at constant temperature during the work.
- ◆ Easy operate. One well trained worker can operate two lines at same time.
- ◆ Toughened glass, curved design, beautiful appearance, high transparency, easy to observe equipment operation, isolate the machine and the outside, dust-proof and protect workers.